
Advanced Technology Microwave Sounder (ATMS) Sensor Data Record (SDR) Error Budget

ATMS SDR Science Team
December 18, 2013

1. Radiometric Calibration Accuracy

1.1 Radiometric Calibration Uncertainty Specification

Table 1. Requirements of ATMS Channel Radiometric Calibration Accuracy [1]

Channel	Accuracy (K)
1-2	1.00
3-15	0.75
16-22	1.00

1.2 Pre-launch Radiometric Uncertainty Budget




Figure.1: Pre-launch radiometric uncertainty budget [2] for the nominal case given as a function of channel index

T_{HTS} : Hot Target Static (HTS) Error

T_{HTD} : Hot Target Dynamic (HTD) Error

T_{CTD} : Cold Target Dynamic (CTD) Error

T_{NLD} : Nonlinearity Dynamic (NLD) Error

T_{PAE} : Planck Approximation Error (PAE)

T_{GDD} : Gain Drift Dynamic (GDD) Error















Figure.2: ATMS channel calibration accuracy: blue – specification values [2, 3]; red – values combined from the above nominal case in Figure 1; green – values obtained from prelaunch Thermal Vacuum (TVAC) calibration test

1.3 Post-launch Radiometric Uncertainty Estimate














Figure.3: ATMS TDR (O), simulation (B) and the difference between O and B under calm, dry clear-sky for all 22 channels























Figure.4: Time series of biases of the daily mean differences between ATMS observations and GPS RO simulations (O-BGPS) [6] calculated for collocated data under clear-sky conditions over ocean and between 60S-60N from December 10, 2011 to December 31, 2012.










Figure.5: ATMS channels 6-13 scatter plot of B^{TDR} against O^{TDR} (left) and scatter plot of B^{SDR} against O^{SDR} (right) from the 86 ARM SGP radiosonde and ATMS matchups.

1.4 Prelaunch Channel Noise Sensitivity (NEDT) from TVAC






















Figure.6: ATMS prelaunch channel NEDT values [4-6]: blue – from specification; red – TVAC at 300 K










Figure.7: NEDT values of all 22 ATMS channels vs. scene temperatures. Data is from TVAC test for ATMS CP is at 5 °C and RC1.

1.5 Post-launch Channel Noise Sensitivity (NEDT) from in-orbit Data




Figure.8: ATMS post-launch in-orbit channel NEDT values computed by the standard deviation and Allan deviation: blue - from standard deviation; red - Allan deviation [7].

1.6 Geolocation




Figure.9: In-track and cross-track mean errors for “edge of scan” geolocation verification analysis: channel 1 ($\pm 0.3^\circ$), channel 3 ($\pm 0.2^\circ$), channel 16 ($\pm 0.2^\circ$), and channel 17 ($\pm 0.1^\circ$)

2. References

- [1] Northrop Grumman Electronic Systems (NGES) technique report 14029B, 2007: Advanced Technology Microwave Sounder (ATMS) Calibration Data Book ATMS PFM P/N 1362460-1 S/N 302.
- [2] Northrop Grumman Electronic Systems (NGES) technique report 12110E, 2011: Advanced Technology Microwave Sounder (ATMS) Radiometric Math Model and Source Assurance Package.
- [3] F. Weng, X. Zou, N. Sun, H. Yang, M. Tian, W. Blackwell, X. Wang, L. Lin, and K. Anderson, "Calibration of Suomi National Polar-Orbiting Partnership Advanced Technology Microwave Sounder", *J. Geophys. Res.*, vol. 118, page 1-14, 2013.
- [4] JPSS ATMS ATBD (2011), Joint Polar Satellite System (JPSS) Advanced Technology Microwave Sounder (ATMS) SDR Radiometric Calibration Algorithm Theoretical Basic Document (ATBD).
- [5] JPSS ATMS OAD (2012), Joint Polar Satellite System (JPSS) Operational Algorithm Description (OAD) Document for Advanced Technology Microwave Sounder (ATMS) Sensor Data Record (SDR) Software.
- [6] X. Zou, L. Lin and F. Weng, "Absolute Calibration of ATMS Upper Level Temperature Sounding Channels Using GPS RO Observations", *IEEE Transactions on Geoscience and Remote Sensing*, 2013
- [7] W. Riley, *Handbook of Frequency Stability Analysis*, chapter 5.2, Hamilton Technical Services, 2007